

TECHNICAL SPECS - LIGHT

| | |
|-------------------------------|---|
| Lights network | Subnet mask: 255.255.0.0 IP-Range Desk; 2.0.0.255 |
| FOH | To stage left 2x ethercon RJ45 cat 6a To stage right 2x ethercon RJ45 cat 6a <i>ELC dmxLAN node 3 If necessary lightnetwork is available through DMX.</i> |
| Flybars | ELC dmxLAN Node 8 Flybars: sACN 2 = Flybar 2 sACN 3 = Flybar 4 sACN 4 = Flybar 6 sACN 5 = Flybar 8 sACN 6 = Flybar 10 |
| Stage Left and Right | From FOH left and right 2x ethercon RJ45 cat 6a ELC dmxLAN node 3 Stage left and right |
| Dimming | Our 5 flybars have fixed SRS fixed dimmer channels – 2.3 kW each On stage we can provide 1x SRS 24 dimmer channels – 2.3 kW each Every flybar has two fixed voltage circuits at 240 volt max 2.3 kW each |
| Desk | 1x Avolite Arena Console IP: 2.0.0.35 |
| Titan version | When needed please contact use for our firmware version. |
| Orchestra fixtures sACN 34 | Above the stage are 36 x ETC D60 studio HD HSIC (7DMX) spots, the D60 are fixed in our stage ceiling and are not moveable. |
| Fixed Moving led Fixtures | We can provide a Fixed Robe light set: <ul style="list-style-type: none">• 10x Robe T1 Profile• 6x Robe Spider• 20x Robe 150 Led Beam Fixtures position are fixed on Lx. If you want to use a Lx in other flybars than please contact our production team. |
| Front fixtures sACN 33 | 14x Niethammer HPZ211 profile 2 kW – 10 / 22° 8x Niethammer HPZ215 profile 2 kW – 15 / 40° 1x Robert Juliat Aramis followspot 2,5 kW 12x ETC Source Four LED Serie 3 Lustr X8 – 19° 6x Robe T1 profile |
| Horizon lights | 14 x Robert Juliat LEDhorizon Dalis 860 M2 |
| Other fixtures | On request we can provide conventional fixtures. If needed please contact our production team. |
| Smoke | 1x Swefog Ultimate 3000 |
| DWG | Contact us for our DWG. |

DOWNLOADS

[FULL LIGHT SET-UP FRONT >](#)

[FULL LIGHT SET-UP MOVING LIGHTS >](#)

[RIGGINGSHEET >](#)

TECHNICAL SPECS 2024 - LIGHT
PARKZAAL

MUSIS
STADSTHEATER ARNHEM